







AÇO	DIAM (mm)	C.TOTAL (m)	PESO + 10 % (kg)
CA50	10.0	89.1	60.4
CA60	5.0	111.4	18.9
PESO TOTAL (kg)			
CA50	60.4		
CA60	18.9		

Volume de concreto (C-30) = 0.75 m³
Área de forma = 15.25 m²




	P1	P2	P3
	P4	P5	P6
ACO	N	DIAM	QUANT
			C.U.NIT
		(mm)	(cm)
			C.TOTAL
			(cm)
CA60	1	5.0	48
	2	5.0	8
	3	5.0	56
	4	5.0	96
	5	5.0	68
	6	5.0	16
CA50	1	10.0	24
	2	10.0	300
	3	10.0	7200
	4	10.0	VAR
	5	10.0	VAR
	6	10.0	24

Relação do aço

AÇO	DIAM (mm)	C.TOTAL (m)	PESO + 10 % (kg)
CA50	10,0	89,1	60,4
CA60	5,0	111,4	18,9
PESO TOTAL (kg)			
CA50	60,4		
CA60	18,9		

Volume de concreto (C-30) = 0.75 m³
Área de forma = 15.25 m²



ARMAÇÃO POSITIVA DAS LAJES DO PAVIMENTO TÉRREO (EIXO X)

ESCALA 1:50

[illegible]